Foam Storage Tanks

Foam Bladder Tank | MXC Vertical Carbon Steel - 12 bar or 16 bar - **EN 13445 FM/UL**

SFFF compatible



Related Documents	TD2.3.1.1 (Technical Data Page)
Approvals	UL FM APPROVED CE
Design Code	EN 13445 (PED compliant)
Design Pressure	175 psi (12.1 bar) or 232 psi (16.0 bar)
Volume	25 USG (94 l) to 4,000 USG (15,141 l)
Material (Tank)	Carbon steel
Material (Bladder)	Polyester reinforced hypalon-neoprene polymer or NBR
Finish	Red epoxy (Flame red RAL3000)
Weight	See technical data page
Options	• Pre-piped with proportioner • Additional protective coatings • Ladder, platform, sunshade • Skid mounting See technical data page for complete list

Note: Bladder tank is FM Approved and/or UL Listed as part of a fire extinguishing system combining designated foam concentrates, ratio controllers, ILBP's and discharge devices. Approved and Listed system components can be found at www.approvalguide.com and https://iq.ulprospector.com
Bladder tanks are tested for compatibility with specific foam concentrates as per the technical data page.

Part number		Volume		Part number		Volume	
12.1 bar	16 bar	USG	Litres	12.1 bar	16 bar	USG	Litres
MXCV0025GF	MXCV0025GF-16	25	94	MXCV1200GF	MXCV1200GF-16	1,200	4,542
MXCV0036GF	MXCV0036GF-16	36	136	MXCV1300GF	MXCV1300GF-16	1,300	4,921
MXCV0050GF	MXCV0050GF-16	50	189	MXCV1400GF	MXCV1400GF-16	1,400	5,299
MXCV0075GF	MXCV0075GF-16	75	283	MXCV1500GF	MXCV1500GF-16	1,500	5,678
MXCV0100GF	MXCV0100GF-16	100	378	MXCV1600GF	MXCV1600GF-16	1,600	6,056
MXCV0150GF	MXCV0150GF-16	150	567	MXCV1700GF	MXCV1700GF-16	1,700	6,435
MXCV0200GF	MXCV0200GF-16	200	757	MXCV1800GF	MXCV1800GF-16	1,800	6,813
MXCV0250GF	MXCV0250GF-16	250	946	MXCV1900GF	MXCV1900GF-16	1,900	7,192
MXCV0300GF	MXCV0300GF-16	300	1,135	MXCV2000GF	MXCV2000GF-16	2,000	7,570
MXCV0350GF	MXCV0350GF-16	350	1,324	MXCV2200GF	MXCV2200GF-16	2,200	8,327
MXCV0400GF	MXCV0400GF-16	400	1,514	MXCV2400GF	MXCV2400GF-16	2,400	9,084
MXCV0450GF	MXCV0450GF-16	450	1,703	MXCV2600GF	MXCV2600GF-16	2,600	9,842
MXCV0500GF	MXCV0500GF-16	500	1,892	MXCV2800GF	MXCV2800GF-16	2,800	10,599
MXCV0600GF	MXCV0600GF-16	600	2,271	MXCV3000GF	MXCV3000GF-16	3,000	11,356
MXCV0700GF	MXCV0700GF-16	700	2,649	MXCV3200GF	MXCV3200GF-16	3,200	12,113
MXCV0800GF	MXCV0800GF-16	800	3,028	MXCV3400GF	MXCV3400GF-16	3,400	12,870
MXCV0900GF	MXCV0900GF-16	900	3,406	MXCV3600GF	MXCV3600GF-16	3,600	13,627
MXCV1000GF	MXCV1000GF-16	1,000	3,785	MXCV3800GF	MXCV3800GF-16	3,800	14,384
MXCV1100GF	MXCV1100GF-16	1,100	4,163	MXCV4000GF	MXCV4000GF-16	4,000	15,141

Note: This document contains basic product information only. Information, photos and drawings are not contractually binding.
In all cases, the manufacturer's full technical documentation (see "Related Documents" above) remains the reference document.
Note that certificates, test reports and approvals may be published in the OEM name.
The contents of this publication are subject to modifications without notice. All rights reserved

PS2.3.1.1VF/27092021/en | Rev.21.3

© K.C. Antincendi S.r.l. | Via Pavia 76 | 27042 Bressana Bottarone (PV) | Italy | info@kcantincendi.com